



Super S® Euro SuperSyn™ 5W-40 ACEA C3 Motor Oil

Super S® Euro SuperSyn™ C3 5W-40 Motor Oil is a full synthetic Low Saps engine oil formulated to meet the technical requirements of the most demanding automobile manufacturers including **General Motors, BMW, Volkswagen, Audi, Fiat, Skoda, Mitsubishi, Renault, Mini, Mercedes-Benz, and Honda Kia**. Provides unmatched protection under the most severe conditions including sports driving, city and motorway, off road, and while maintaining the pumping ability for frequent startups.

SuperSyn™ C3 5W-40 Motor Oil is manufactured to our Advanced Quality Assurance™ standards to provide excellent fuel economy while delivering outstanding performance in newer model diesel and gasoline powered engines. It is intended for use as catalyst compatible Oil at extended Drain Intervals in Vehicles with all Types of modern after-treatment systems in High Performance Passenger Car & Light Duty Van Gasoline & DI Diesel Engines

Features

- Excellent protection from deposits at all operating temperatures
- Extends the service life of post-treatment systems by preventing DPFs and catalytic converters from clogging
- Increased fuel mileage
- Excellent protection against accelerated oil consumption
- State of the Art emissions control lowering emissions of NOx, CO₂, CO particles

Benefits:

- Eco-friendly Mid-SAPS formula
- Robust package allows extended drain even under the harshest driving conditions
- Improved fuel mileage
- Most shear stability for maximum protection
- After-treatment compatibility

Applications

Euro SuperSyn™ C3 5W-40 Motor Oil are full synthetic motor oils featuring advanced viscosity control and shear stability. They maintain performance in the harshest conditions and for extended oil drain intervals for use wherever ACEA C3-16 or API-SN/CF or previous motor oil specifications are called for. Euro SuperSyn™ C3 also meets the performance requirements of the below OEMs.

Porsche A40	MB 229.31/226.5/229.51
Ford WSS-M2C917-A	BMW LL-04
Renault 0700/0710	Fiat 9.55535-S2
VW 502.00/505.01	dexos 2
SAE J2363	

TYPICAL CHARACTERISTICS

Super S® Euro SuperSyn™ C3 Full Synthetic		
Properties	Test Method ASTM D-	Typical Results
SAE Viscosity Grade		5W-40
Viscosity		
cSt @ 40°C		84.1
cSt @ 100°C	445	14.8
Viscosity Index	2270	174
CCS Viscosity (mPa·s)	5293	6600@-30C
NOACK Volatility (%wt)	5800	13.0
Color ASTM		4.5

Typical Characteristics are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.